



**DECLARATION OF PERFORMANCE**

According to Annex III of the Regulation (EU) no 305/2011

**ARBO XL1075**

**DOP 2014-AR107519**

**EN15651 -1: F – INT**

**Sealant for Façade Elements for interior application.**

Contact address of the manufacturer:

**Adshead Ratcliffe and Co Ltd  
Derby Road  
Belper  
Derby  
DE56 1WJ**

Verification of constancy of performance of the construction product as set out in Annex V:

The Notified Body 4ward Testing, Identification Number **NB2538**, performed the determination of the product type on the basis of type testing under System 3 and issued:

Report Number: NLR1773

The performance of the product identified is in conformity with the declared performance (see below). This Declaration of Performance is issued under the sole responsibility of the Manufacturer

Signed for and on behalf of the manufacturer by;

Steven Brown, Technical Director, Adshead Ratcliffe and Co Ltd,  
Belper  
30<sup>th</sup> June 2014



**ARBO XL1075 – Declared Performance**



**EN 15651-1:F – INT  
CLASS – 7.5P**

**Preconditioning: Method A + B (according to ISO 8340)**

**Substrate: Mortar with Arbo 2650 Primer**

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to Fire (EN 13501)	Class E	EN15651-1:2012
Release of chemicals dangerous to the environment and health	See product Material Safety Data Sheet	
Water tightness and air tightness		
Resistance to Flow (ISO 7390)	$\leq 3$ mm	
Loss of Volume (ISO 10563)	$\leq 25$ %	
Determination of Elastic Recovery (ISO 7389)	$\leq 40$ %	
Determination of Tensile Properties – Extension to Break (ISO 8339)	$\geq 25$ %	
Determination of Adhesion/Cohesion after Immersion in Water (ISO 10591)	$\geq 25$ %	
Durability	Pass	