



DECLARATION OF PERFORMANCE

According to Annex III of the Regulation (EU) no 305/2011

ARBOCAULK

DOP 2014-ARCA20

EN15651 -1: F – INT

Sealant for Façade Elements for interior application.

Contact address of the manufacturer:

**Adshead Ratcliffe and Co Ltd
Derby Road
Belper
Derby
DE56 1WJ**

Verification of constancy of performance of the construction product as set out in Annex V:

The performance of the product identified is in conformity with the declared performance (see below). This Declaration of Performance is issued under the sole responsibility of the Manufacturer

Signed for and on behalf of the manufacturer by;

Steven Brown, Technical Director, Adshead Ratcliffe and Co Ltd,
Belper
23rd September 2014



ARBOCAULK – Declared Performance



**EN 15651-1:F – INT
CLASS – 7.5P**

Preconditioning: Method A + B (according to ISO 8340)

Substrate: Mortar with Arbo 2650 Primer

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to Fire (EN 13501)	Class E	EN15651-1:2012
Release of chemicals dangerous to the environment and health	See product Material Safety Data Sheet	
Water tightness and air tightness		
Resistance to Flow (ISO 7390)	≤ 3 mm	
Loss of Volume (ISO 10563)	≤ 25 %	
Determination of Elastic Recovery (ISO 7389)	≤ 40 %	
Determination of Tensile Properties – Extension to Break (ISO 8339)	≥ 25 %	
Determination of Adhesion/Cohesion after Immersion in Water (ISO 10591)	≥ 25 %	
Durability	Pass	