



**DECLARATION OF PERFORMANCE**

According to Annex III of the Regulation (EU) no 305/2011

**ARBOKOL AG2 GUN GRADE**

**DOP 2014-ARAG2GG16**

**EN15651 -1: F – EXT-INT**

**Sealant for Façade Elements for exterior and interior application.**

Contact address of the manufacturer:

**Adshead Ratcliffe and Co Ltd  
Derby Road  
Belper  
Derby  
DE56 1WJ**

Verification of constancy of performance of the construction product as set out in Annex V:

The Notified Body 4ward Testing, Identification Number **NB2538**, performed the determination of the product type on the basis of type testing under System 3 and issued:

Report Number: NLR1789

The performance of the product identified is in conformity with the declared performance (see below). This Declaration of Performance is issued under the sole responsibility of the Manufacturer

Signed for and on behalf of the manufacturer by;

Steven Brown, Technical Director, Adshead Ratcliffe and Co Ltd,  
Belper  
25<sup>th</sup> June 2014



**ARBOKOL AG2 GUN GRADE – Declared  
Performance**



**EN 15651-1:F – EXT-INT  
CLASS – 25LM**

**Preconditioning: Method A (according to ISO 8340)**

**Substrate: Mortar with Arbokol AG2 Porous Primer**

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to Fire (EN 13501)	NPD	EN15651-1:2012
Release of chemicals dangerous to the environment and health	See product Material Safety Data Sheet	
Water tightness and air tightness		
Resistance to Flow (ISO 7390)	$\leq 1$ mm	
Loss of Volume (ISO 10563)	$\leq 10$ %	
Determination of Tensile Properties at Maintained Extension after Immersion in Water (ISO 10590)	Pass	
Secant Tensile Modulus at + 23 ± 2°C (ISO 8339)	$\leq 0.4$ Mpa	
Secant Tensile Modulus at - 20 ± 2°C (ISO 8339)	$\leq 0.6$ Mpa	
Durability	Pass	