



DECLARATION OF PERFORMANCE

According to Annex III of the Regulation (EU) no 305/2011

ARBOMERIC MP20

DOP 2016-ARMP2025

**EN15651 -4: PW- EXT - INT
Sealants for Pedestrian Walkways**

Contact address of the manufacturer:

**Adshead Ratcliffe and Co Ltd
Derby Road
Belper
Derby
DE56 1WJ**

Verification of constancy of performance of the construction product as set out in Annex V:

The Notified Body 4ward Testing, Identification Number **NB2538**, performed the determination of the product type on the basis of type testing under System 3 and issued:

Report Number: NLR1928

The performance of the product identified is in conformity with the declared performance (see below). This Declaration of Performance is issued under the sole responsibility of the Manufacturer

Signed for and on behalf of the manufacturer by;

Steven Brown, Technical Director, Adshead Ratcliffe and Co Ltd,
Belper
23rd June 2016



ARBOMERIC MP20 – Declared Performance



**EN 15651-4: PW – EXT-INT
CLASS – 20HM**

Preconditioning: Method A (according to ISO 8340)

Substrate: Mortar with Arbo 2650 Primer

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to Fire (EN 13501)	NPD	EN15651-4:2012
Release of chemicals dangerous to the environment and health	See product Material Safety Data Sheet	
Water tightness and air tightness		
Loss of Volume (ISO 10563)	$\leq 10 \%$	
Determination of Tensile Properties at Maintained Extension (ISO 8340)	Pass	
Determination of Tensile Properties at Maintained Extension (ISO 8340 - Modified) – Tear Resistance	Pass	
Determination of Tensile Properties at Maintained Extension after Immersion in Water (ISO 10590 - Modified) – Extended Soak in Distilled Water	Pass	

Determination of Tensile Properties at Maintained Extension after Immersion in Water (ISO 10590 Modified) – Extended Soak in Salt Water	Pass	
Durability	Pass	