

Arbo Small Gap Sealer

Arbo Small Gap Sealer is a low viscosity PVC adhesive and gap filler. The product forms a permanent bond to PVCu, Polycarbonate and many other plastics. Arbo Small Gap Sealer also has excellent adhesion to glass, aluminium and many other common construction substrates.

MAIN APPLICATIONS

Recommended for sealing mitre joints, cleats, screws and hinges in window and door assemblies. Recommended for joints up to 3 mm width.

APPLICATION INSTRUCTIONS

The joint surfaces must be clean, dry and free from all contamination. The surfaces should be degreased using the appropriate Arbo Cleaner. It is recommended that Adshedd Ratcliffe Technical Services Department be contacted to discuss effect of solvents on sensitive plastics.

TECHNICAL DATA

Work Life:	Product skins over within 5 minutes at 20° C
Solids Content:	53 % ± 3 %
Application Temperature:	+ 5° C to + 30° C
Service Temperature:	- 10° C to + 80° C
UV Resistance:	Good
Shelf Life:	9 months



PACKAGING

300 ml cartridge.
500 ml Tin (Plews Applicator gun available to purchase separately if required).

COLOURS

White, Clear

HEALTH AND SAFETY

Product contains solvents. Please refer to Material Safety Data Sheet for full information

IMPORTANT: The information in this leaflet is given in good faith and based on results gained from experience and tests. However, all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control. Goods are supplied subject to the Company's terms and conditions of sales, a copy of which is available on request.

CARLISLE® Adshead Ratcliffe & Co Ltd. United Kingdom

Derby Road | Belper
Derbyshire

DE56 1WJ
United Kingdom

T +44 (0)1773 826661
F +44 (0)1773 821215

E arbo@arbo.co.uk
www.arbo.co.uk